

## **Listing of Claims:**

- (Currently Amended) A method of keeping a session active and connected with a
  mobile device while changing data communications networks, comprising the steps of:
  - receiving packets, associated with a session, over a first connection in a first data communications network wherein said first connection is handled by a first gateway associated with said first data communications network;
  - requesting a second connection with a second data communications network while said mobile device is moving towards the second network;
  - acquiring an address of a second gateway associated with the second data communications network and assigned to handle said second connection;
  - establishing a tunnel between a first said first gateway associated with the first data communications network serving said first connection and said second gateway;
  - routing packets, associated with said session, by said first gateway over said established tunnel to said second gateway and over the second connection based on the acquired gateway address to said mobile device.
- 2. (Previously Presented) The method of claim 1, wherein an entity in the second data communications network initiates the request for the establishment of said tunnel.
- 3. (Previously Presented) The method of claim 1, wherein said first gateway in the first data communications network initiates the request for the establishment of said tunnel.
- 4. (Previously Presented) The method of claim 1, wherein mobile device initiates the request for the second connection.

Page 2 of 8

Appl. No. 09/416,757 AmdL Dated November 3, 2003 Reply to Office action of August 6, 2003 Attorney Docket No. P12128-2/040010-440 EUS/J/P/03-6084

## 5-7. (Cancelled)

- 8. (Previously Presented) The method of claim 2 wherein said second gateway provides the network identity associated with said second gateway to said first gateway.
- 9. (Previously Presented) The method of claim 2 wherein said second gateway retrieves the network identity associated with said first gateway from a centralized database.
- 10. (Previously Presented) The method of claim 1 wherein said first gateway is a Gateway General Packet Radio Services Serving Node (GGSN).
- 11. (Previously Presented) The method of claim 3 wherein said first gateway provides the network identity as sociated with said first gateway to said second gateway.
- 12. (Previously Presented) The method of claim 3 wherein said first gateway buffers data intended for said mobile device until said tunnel has been established with said second gateway.
- 13. (Previously Presented) The method of claim 4 wherein said mobile device provides the first data communications network with the network identity associated with said second gateway.
- 14. (Previously Presented) The method of claim 4 wherein said mobile device provides the second data communications network with the network identity associated with said first gateway.



Chart

Appl. No. 09/416,757 Amdt. Dated November 3, 2003 Reply to Office action of August 6, 2003 Attomey Qocket No. P12128-2/040010-440 EUS/J/P/03-6084

15. (Previously Presented) The method of claim 1 wherein said first data communications network communicates with said second data communications network using an Mobilel Pprotocol.

16-19. (Cancelled)